

CloudDC SuperServer SYS-112C-TN

1U UP CloudDC with DC-MHS, up to 12 hot-swap 2.5" NVMe/SAS/SATA bays and 2 PCIe 5.0 x16 slots + 1 PCIe 5.0 x16 AIOM slot



More details here

Key Applications

Virtualization, HPC, CDN, Edge Nodes, Cloud Computing, Data Center
Optimized, Storage Headnode,

Key Features

- All-in-one platform for cloud data centers, based on the OCP Data Center Modular Hardware System (DC-MHS) with flexible I/O and storage configurations
Based on Modular Scalable DeNsity Optimized HPM Form Factor (M-SDNO)
Support DC-SCM module with OpenBMC;
- Single Intel® Xeon® 6 6700 series processor with E-cores;
- 16 DIMM slots supporting up to 1TB of memory (6700E series CPU);
- Support FH DPU and single slot GPU;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible).;
- Breeze through high throughput workloads with PCIe 5.0 NVMe drive support;
- Trusted Platform Module (TPM) 2.0 onboard;



Form Factor	1U Rackmount Enclosure: 437 x 43 x 747mm (17.2" x 1.7" x 29.4") Package: (23.8" x 8.1" x 40.6")
Processor	Single Socket E2 (LGA-4710) Intel® Xeon® 6 6700 series processors with E-cores Up to 144C/144T; Up to 108MB Cache
GPU	Max GPU Count: Up to 2 single-width GPU(s) CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect
System Memory	Slot Count: 16 DIMM slots/8 Channels Max Memory (1DPC): Up to 1TB 6400MT/s ECC DDR5 RDIMM Max Memory (2DPC): Up to 1TB 5200MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 8 bay(s) <ul style="list-style-type: none"> • 8 front hot-swap 2.5" PCIe 5.0 NVMe/SAS*/SATA* drive bay(s) Option A: Total 12 bay(s) <ul style="list-style-type: none"> • 8 front hot-swap 2.5" PCIe 5.0 NVMe*/SAS*/SATA* drive bay(s) • 4 front hot-swap 2.5" SAS*/SATA* drive bay(s) (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 2 M.2 PCIe 5.0 x2 NVMe slot(s) (M-key 2280(default)/22110; VROC required for RAID)
Expansion Slots	Default <ul style="list-style-type: none"> • 2 PCIe 5.0 x16 FHHL slot(s) • 1 PCIe 5.0 x16 AIOM slot(s) (OCP 3.0 compatible)
On-Board Devices	NVMe: NVMe; RAID 0/1/5/10 support(Intel® VROC RAID key required) Chipset: System on Chip Network Connectivity: Via Slim-AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s) USB: 2 USB 3.2 Gen1 Type-A port(s) (rear) Video: 1 Mini-DP port(s) (Rear) TPM: 1 TPM header


(Front View – System)



Drive Bay	Description
1 - 7	8 Hot-swap 2.5" PCIe 5.0 NVMe/SAS/SATA ³ Drive Bays
8 - 11	4 Hot-swap 2.5" PCIe 5.0 SAS/SATA ³ Drive Bays (optional)

* NVMe/SAS/SATA³ support requires additional parts from the optional parts list

(Rear View – System)



Slot Description	
1 - 2	PCIe 5.0 x16 FRHLL
3	PCIe 5.0 x16 A1OM (OCP 3.0)

System Cooling	Fans: 8 Counter-Rotating PWM 40x40x56mm Fan(s)
Power Supply	2x 1000W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 47 lbs (21.3 kg) Net Weight: 31 lbs (14.1 kg) Available Color: Black
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	Super X14SBHM
Chassis	CSE-MD101TS-R000NDP