

Hyper SuperServer SYS-120H-TNR

1U Hyper with 8 NVMe/SAS/SATA bays




More details here

Key Applications

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server,

Key Features


- Dual Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable Processors;
- 32 DIMM Slots; Up to 8TB DRAM; Up to 8TB Intel® Optane™ Persistent Memory (up to 12TB with DRAM); 3200/2933/2666 ECC DDR4 LRDIMM; RDIMM; Intel® Optane™ Persistent Memory 200 series;
- 3 PCIe 4.0 x16 slots with support for GPU/Accelerator cards;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible);
- 8x 2.5" hot-swap NVMe/SATA/SAS drive bays; Optional 4x 2.5" hot-swap NVMe/SAS/SATA drive bays; 2x internal M.2 NVMe/SATA drive slots; Optional RAID support via storage add-on card;
- 8 heavy duty hot-swap fans with optimal fan speed control;



| | |
|--------------------------|--|
| Form Factor | 1U Rackmount Enclosure: 437 x 43 x 747mm (17.2" x 1.7" x 29.4") Package: 605 x 206 x 1032mm (23.8" x 8.1" x 40.6") |
| Processor | Dual Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable processors Up to 40C/80T; Up to 60MB Cache per CPU |
| GPU | Up to 2 double-width GPU(s) |
| System Memory | Slot Count: 32 DIMM slots Max Memory (2DPC): Up to 8TB 3200MT/s ECC DDR4 Supports Intel® Optane™ persistent memory 200 series |
| Drive Bays Configuration | Default: Total 8 bay(s) • 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s) Option A: Total 12 bay(s) • 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s) (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 2 M.2 NVMe/SATA slot(s) (M-key 2280/22110) |
| Expansion Slots | Default • 1 PCIe 4.0 x16 FHHL slot(s) • 2 PCIe 4.0 x16 FH/10.5"L slot(s) • 1 PCIe 4.0 x16 AIOM slot(s) (OCP 3.0 compatible) |
| On-Board Devices | SATA: SATA (6Gbps) ; RAID 0/1/5/10 support NVMe: NVMe; RAID 0/1/5/10 support(Intel® VROC RAID key required) Chipset: Intel® C621A Network Connectivity: 2 RJ45 1GbE with Intel® I350-AM2 (optional) 4 RJ45 1GbE with Intel® I350-AM4 (optional) 4 SFP 1GbE with Intel® I350-AM4 (optional) 2 RJ45 10GBASE-T with Intel® X550-AT2 (optional) 2 SFP+ 10GbE with Intel® X710-BM2 (optional) 4 SFP+ 10GbE with Intel® XL710-BM1 (optional) 4 SFP+ 10GbE with Intel® X710-TM4 (optional) 2 SFP28 25GbE with Broadcom® BCM57414 (optional) 4 SFP28 25GbE (optional) 2 QSFP28 100GbE with Broadcom® BCM57508 (optional) |
| Input / Output | LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s) |

USB: 2 USB 3.0 port(s) (rear)
1 USB 3.0 port(s) (front)
Video: 1 VGA port(s)

(Front View – System)



| Slot | Description |
|-------|--|
| 1 – 2 | 2.5" Hot-swap NVMe/SAS3/SATA3 Drive Bays (NVMe from CPU1)* |
| 3 – 4 | 2.5" Hot-swap NVMe/SAS3/SATA3 Drive Bays (NVMe from CPU2)* |

*NVMe, SAS3, or SATA3 support requires additional parts in optional parts list

(Rear View – System)



| Slot | Description |
|------|---------------------------------|
| A | AIOM / OCP 3.0 NIC Slot |
| 1 | PCI-E 4.0 x16 Slot (FH, 6.6'L) |
| 2 | PCI-E 4.0 x16 Slot (FH, 10.5'L) |
| 3 | PCI-E 4.0 x16 Slot (FH, 10.5'L) |

CPU CPU

| | |
|-----------------------|--|
| System Cooling | Fans: 8 counter-rotating 40x40x56mm Fan(s) |
| Power Supply | 2x 1200W Redundant Titanium Level (96%) Hot-plug power supplies |
| System BIOS | BIOS Type: AMI 256MB SPI Flash |
| Management | SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New! |
| PC Health Monitoring | CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 49 lbs (22.2 kg) Net Weight: 34 lbs (15.4 kg) Available Color: N/A |
| Operating Environment | Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing) |
| Motherboard | Super X12DHM-6 |
| Chassis | CSE-HS119-R1K24P |