

# Hyper SuperServer SYS-212H-TN

2U UP Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and up to 3 PCIe 5.0 + 1 PCIe 5.0 AIOM slots



More details here

## Key Applications

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server, Data Center Optimized, Database Processing and High Density Storage,

## Key Features



- Hyper is a flagship performance rackmount server designed for scale-out cloud workloads.;
- Single Intel® Xeon® 6 Processor.;
- 16 DIMM slots supporting up to 1TB of memory (6700E series CPU).;
- Double width add-on card support.;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible).;
- Breeze through high throughput workloads with PCIe 5.0 NVMe drive support.;
- Trusted Platform Module (TPM) 2.0 onboard.;
- Modularized and Tool-less design for easy serviceability.;



Form Factor	2U Rackmount Enclosure: 437 x 88.9 x 806.2mm (17.2" x 3.5" x 31.74") Package: 672 x 253 x 1100mm (26.46" x 9.96" x 43.31")
Processor	Single Socket E2 (LGA-4710) Intel® Xeon® 6 6700 series processors with E-cores Up to 144C/144T; Up to 108MB Cache
GPU	Max GPU Count: Up to 1 double-width or 2 single-width GPU(s) CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 1TB 6400MT/s ECC DDR5 RDIMM Max Memory (2DPC): Up to 1TB 5200MT/s ECC DDR5 RDIMM
Drive Bays Configuration	Default: Total 8 bay(s) <ul style="list-style-type: none"> <li>• 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s)</li> </ul> Option A: Total 16 bay(s) <ul style="list-style-type: none"> <li>• 8 front hot-swap 2.5" PCIe 5.0 x4 NVMe* drive bay(s)</li> <li>• 8 front hot-swap 2.5" SAS*/SATA* drive bay(s)</li> </ul> Option B: Total 16 bay(s) <ul style="list-style-type: none"> <li>• 16 front hot-swap 2.5" SAS*/SATA* drive bay(s)</li> </ul> Option C: Total 24 bay(s) <ul style="list-style-type: none"> <li>• 24 front hot-swap 2.5" SAS*/SATA* drive bay(s)</li> </ul> (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 2 M.2 NVMe slot(s) (M-key 2280/22110/25110; VROC required for RAID)
Expansion Slots	Option A <ul style="list-style-type: none"> <li>• 1 PCIe 5.0 x16 FHFL double-width slot(s)</li> <li>• 1 PCIe 5.0 x16 FH/10.5"L double-width slot(s)</li> <li>• 1 PCIe 5.0 x16 AIOM slot(s) (OCP 3.0 compatible)</li> </ul> Option B <ul style="list-style-type: none"> <li>• 1 PCIe 5.0 x16 FHFL double-width slot(s)</li> <li>• 2 PCIe 5.0 x8 FH/10.5"L slot(s)</li> <li>• 1 PCIe 5.0 x16 AIOM slot(s) (OCP 3.0 compatible)</li> </ul>
On-Board Devices	NVMe: NVMe; RAID 0/1/5/10 support(Intel® VROC RAID key required) Chipset: System on Chip Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s)

USB: 2 USB 3.0 port(s) (rear)  
Video: 1 VGA port(s)

---



System Cooling	Fans: 6 counter-rotating 60x60x56mm Fan(s) Air Shroud: 1 CPU Air Shroud(s)
Power Supply	2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 64MB SPI Flash
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 75 lbs (34 kg) Net Weight: 45 lbs (20.5 kg) Available Color: Silver
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<a href="#">Super X14SBH</a>
Chassis	<b>CSE-HS201-R000NFP</b>