

# BigTwin SuperServer SYS-621BT-DNC8R

2U 2-Node BigTwin with 6 hot-swap 3.5" NVMe/SAS/SATA drives per node



More details here

## Key Applications

Hyperconverged Infrastructure, Scale-Out Object Storage, Back-up & Recovery,

## Key Features

- Socket E (LGA 4677) support 5th/4th Gen Intel® Xeon® Scalable processors;
- Intel® C741;
- 16 DIMM Slots supporting up to 4TB of memory; ECC RDIMMs up to DDR5-5600;
- Internal PCIe 4.0 x8 for 2 M.2 NVMe support onboard  
1 PCIe 5.0 x16 (LP) slot; 2 PCIe 5.0 x8 (LP) slot; Tool-less support  
Optional M.2 (22x80) HW RAID1 NVMe Boot Controller via SCC-A2NM2241G3-B1;
- Network connectivity via AIOM (OCP 3.0 compliant);
- Built-in SAS3 Support via Broadcom 3808; IT Mode  
6 Hot-Swap 3.5" drive bays (2x PCIe 5.0 NVMe/SAS and 4x PCIe 4.0 NVMe/SAS);
- Liquid Cooling Support  
4 cooling fans per 2U enclosure, 14.9K RPM; Shared Cooling Design;
- 2200W Redundant Power Supplies Titanium Level (96%+); Shared Power Design;



- Two **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports 2U Rackmount

Enclosure: 449 x 88 x 774mm (17.68" x 3.47" x 30.5")  
Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")

**Processor** Dual Socket E (LGA-4677)  
5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors  
Supports Intel Xeon CPU Max Series with high bandwidth memory (HBM)  
Up to 64C/128T; Up to 320MB Cache per CPU

**GPU** Up to 1 double-width or 1 single-width GPU(s)



**System Memory** Slot Count: 16 DIMM slots  
Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM

**Drive Bays Configuration** Default: Total 6 bay(s)  
• 2 front hot-swap 3.5" PCIe 5.0 NVMe/SAS drive bay(s)  
• 4 front hot-swap 3.5" PCIe 4.0 NVMe/SAS drive bay(s)  
M.2: 2 M.2 PCIe 4.0 x4 NVMe slot(s) (M-key 22110(default); VROC required for RAID)

**Expansion Slots** Default  
• 2 PCIe 5.0 x8 LP slot(s)  
• 1 PCIe 5.0 x16 LP slot(s)

**On-Board Devices** SAS: SAS (12Gbps) via Broadcom® 3808; (IT mode)  
Chipset: Intel® C741  
Network Connectivity: Via AIOM

**Input / Output** LAN: 1 RJ45 1 GbE Dedicated BMC LAN port(s)  
USB: 2 USB 3.0 Gen2 Type-A port(s) (Rear)  
Video: 1 VGA port(s)



System Cooling	Fans: 4x 14.9K RPM Heavy Duty 8cm Fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)
Power Supply	2x 2200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment CPU: Monitors for CPU Cores, Chipset Voltages, Memory. 8+4 Phase-switching voltage regulator
Dimensions and Weight	Weight: Gross Weight: 80.7 lbs (36.6 kg) Net Weight: 55.1 lbs (25 kg) Available Color: Black front & silver body
Operating Environment	RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	<a href="#">Super X13DET-B</a>
Chassis	CSE-827BD2-R2K22P